

Ericson NEMA Chart



Face View	NEMA	Electrical Ratings		PERMA-TITE® 2		PERMA-GRIP™	
	Configuration	Amps	Volts	Plugs	Connectors	Plugs	Connectors
2-pole, 3-Wire Grounding							
	5-15	15	125	1510-PW6P	1610-CW6P	1510-PG	1610-CG
	5-20	20	125	1512-PW6P	1612-CW6P	1512-PG	1612-CG
	6-15	15	250	1514-PW6P	1614-CW6P	1514-PG	1614-CG
	6-20	20	250	1516-PW6P	1616-CW6P	1516-PG	1616-CG
	L5-15	15	125	1520-PW6P	1620-CW6P	1520-PG	1620-CG
	L6-15	15	250	1522-PW6P	1622-CW6P	1522-PG	1622-CG
	L7-15	15	277	1524-PW6P	1624-CW6P	1524-PG	1624-CG
	L5-20	20	125	2310-PW6P	2410-CW6P	2310-PG	2410-CG
	L6-20	20	250	2312-PW6P	2412-CW6P	2312-PG	2412-CG
	L7-20	20	277	2314-PW6P	2414-CW6P	2314-PG	2414-CG
3-Pole, 3-Wire Non-Grounding							
	Non-NEMA	20	125/250	2316-PW6P	2416-CW6P	2316-PG	2416-CG
	Non-NEMA	20/10	205/600	2317-PW6P	2417-CW6P	2317-PG	2417-GC
	Non-NEMA	15A/10A	125V/250V	1507-PW6P	1607-CW6P	1507-PG	1607-CG
3-Pole, 4-Wire Grounding							
	L14-20	20	125/250	2320-PW6P	2420-CW6P		
	L15-20	20	250, 3Ø	2322-PW6P	2422-CW6P		
	L16-20	20	480, 3Ø	2324-PW6P	2424-CW6P		
2-Pole, 3-Wire Grounding							
	L5-30	30	125	2510-PW6P	2610-CW6P	2510-PG	2610-CG
	L6-30	30	250	2512-PW6P	2612-CW6P	2512-PG	2612-GC
	L7-30	30	277	2514-PW6P	2614-CW6P	2514-PG	2614-CG
3-Pole, 3-Wire Non-Grounding							
	Non-NEMA	30	125/250	2516-PW6P	2616-CW6P	2516-PG	2616-CG
3-Pole, 4-Wire Grounding							
	L14-30	30	125/250 3Ø	2520-PW6P	2620-CW6P		
	L15-30	30	250, 3Ø	2522-PW6P	2622-CW6P		
	L16-30	30	480, 3Ø	2524-PW6P	2624-CW6P		
	L17-30	30	600, 3Ø	2526-PW6P	2626-CW6P		
4-Pole, 4-Wire							
	L18-30	30	120/208 3Ø wye	2530-PW6P	2630-CW6P		
4-Pole, 4-Wire Non-Grounding							
	Non-NEMA	30	120/208 3Ø wye	2528-PW6P	2628-CW6P		

Face View	PERMA-LINK®		Economy Grade*		Smart Monitor*		Single Outlet	Male Inlets	Dual Recept (PWDX)
	Plugs	Connectors	Plugs	Connectors	Plugs	Connectors	FS Cover Plates		Receptacle with Cover
2-pole, 3-Wire Grounding									
	1510-P	1610-C	5266-E	5269-E	1510-PXX	1610-CXX	2715-FS10	2705-15/A	1610-PWDX
	1512-P	1612-C			1512-PXX	1612-CXX	2715-FS12	2705-20/A	1612-PWDX
	1514-P	1614-C	Note: Lighted power-on glow models also: 5266-EL & 5269-EL				2715-FS14		1614-PWDX
	1516-P	1616-C					2715-FS16		1616-PWDX
	1520-P	1620-C					2715-FS20	2705-L15/A	1620-PWDX
	1522-P	1622-C					2715-FS22		1622-PWDX
	1524-P	1624-C			2715-FS24		1624-PWDX		
	2310-P	2410-C			2310-PXX	2410-CXX	2820-FS10	2705-L20	6200 Series Boxes For FS Series & PWDX Series • Rubberized • Fully Enclosed • Single and Double Sided • Standard and Deep
	2312-P	2412-C					2820-FS12		
	2314-P	2414-C					2820-FS14		
	2316-P	2416-C					2820-FS16		
3-Pole, 3-Wire Non-Grounding									
	2317-P	2417-C					2820-FS17		
	1507-P	1607-C					2715-FS07		
3-Pole, 4-Wire Grounding									
	2320-P	2420-C					2920-FS20	2705-L142	
	2322-P	2422-C					2920-FS22		
	2324-P	2424-C					2920-FS24	2705-L162	
2-Pole, 3-Wire Grounding									
	2510-P	2610-C					2830-FS10	2705-L30	
	2512-P	2612-C					2830-FS12		
	2514-P	2614-C					2830-FS14		
3-Pole, 3-Wire Non-Grounding									
	2516-P	2616-C					2830-FS16		
3-Pole, 4-Wire Grounding									
	2520-P	2620-C					2930-FS20	2705-L143	
	2522-P	2622-C					2930-FS22		
	2524-P	2624-C					2930-FS24	2705-L163	
	2526-P	2626-C					2930-FS26	2705-L173	
4-Pole, 4-Wire									
	2530-P	2630-C					2930-FS30		
4-Pole, 4-Wire Non-Grounding									
	2528-P	2628-C					2930-FS28		



***Part Number Note for Smart Monitors:**

PLUGS (-PXX)

PML
Perma-Link® Style

PMGL
Perma-Grip™ Style

PW6PL
Perma-Tite®2 Style

CONNECTORS (-CXX)

CML
Perma-Link® Style

CMGL
Perma-Grip™ Style

CW6PL
Perma-Tite®2 Style

